



## PT-60 Mobile Computer

The PT-60 Mobile Computer is a powerful wireless handheld computing device based on the Windows CE® operating system. The ergonomic, compact and durable PT-60 features a bright 2.4-inch TFT 240 x 320 QVGA display with touch screen, a high performance barcode scan engine, wireless communication support including Bluetooth and high speed wireless LAN 802.11b/g, and external USB and RS-232 interfaces. Memory capability includes 128MB DRAM, 128 MB Nand Flash, and one standard SD card slot for expanded memory space demands.

Lightweight at only 250g, the ergonomic PT-60 has an optional pistol grip for ease of scanning. Shockproof, dustproof, and waterproof in compliance with IP54 standards the PT-60 is built for rough environments. For generic applications, the PT-60 comes with a standard, comprehensive software developer kit (SDK) that supports a variety of I/O driver APIs. Accessories include a charging and communication cradle, a pistol grip, charging and communication cable and a four slot battery charger. The PT-60 is suitable for a wide variety of applications including retail, distribution, warehouse, and logistics.

PT-60 mobile computer has received the 2010 Taiwan Excellence Award, the highest accolade presented to Taiwan products. It was judged on criteria that included R&D, Design, Quality, and Marketing. Won this award is just an extra evidence that PT-60 does deliver world-class quality and outstanding performance for a broad range of data collection applications.



### Key Features

- Microsoft Windows CE 5.0
- Sharp and bright color TFT QVGA display with touch screen
- Ergonomic, compact, robust and lightweight
- Bluetooth, 802.11b/g technology
- 1.2 m (4 ft) drop resistance
- IP54 protection class
- User-accessible memory slot
- Quick attach handle
- Extremely long operation hours



Model	PT-60	PT-6300	PT-6010	PT-6310	PT-6020	PT-6320
<b>Wireless Communication</b>						
WPAN	-		Bluetooth Class2, version 1.2		-	
WLAN	-		-		Wi-Fi 802.11b/g	
<b>External I/O interface</b>						
	USB / RS-232(4 Wires)					
<b>Expansion slot</b>						
	Standard SD					
<b>General Characteristics</b>						
OS	WinCE 5.0					
CPU	ARM9 Core 266MHz					
RAM	128MB Mobile DDRAM					
ROM	128MB Nand Flash					
Display	2.4" LCD TFT Transmissive, 240 x 320 QVGA 65K colors with Touch panel					
LED	Blue, Green and Red					
Keypad	29 Numeric					
Alert	Speaker, Vibrator					
Dimensions	168.8mm (L) x 70.1mm (W) x 34.0mm (H)					
Weight	250g (including battery)					
<b>Power</b>						
Battery	1) Mobile Computer: Rechargeable 3.7V 1950mAh Li-Polymer Battery 2) Optional Pistol Grip: Rechargeable 3.7V 4400mAh Li-ion Battery					
Power	Power supply: DC 5V 3A AC Power 100-240V 0.5A, 50-60Hz, 33-48VA					
<b>Scanner</b>						
Scanner system	Long Range CCD scanner 2048 pixels					
Resolution	0.127mm (5mil) at PCS 90%					
Depth of field	600mm (code 39, 20mils, PCS 90%)					
Scanning rate	400 scans /sec					
Decode capability	Auto discriminates all standard one-dimension barcodes; including GS1 databar. Other symbologies can be ordered optionally (2D Symbology – UCC/EAN-Composite, Code 16K, PDF417, Micro PDF 417 for PT-6300, PT-6310 and PT-6320)					
<b>Developing tools</b>						
	embedded Visual C++ 4.0, Visual Studio.NET, Visual Studio 2005, Windows CE SDK					
	Scanner Configuration Utility					
<b>Physical and Environment</b>						
Operating Temperature	-10°C to 60°C / 14°F to 140°F					
Storage Temperature	-20°C to 70°C / -4°F to 158°F					
Humidity	1) Operating: Non-condensed 10-90%      2) Storage: Non-condensed 5-95%					
Impact resistance	1) 1.2M/4ft (Terminal) 0.9M/3ft (Cradle)/(4 drops per 6 sides)      2) IP54					
Electrostatic discharge	1) +/- 15 KV air discharge      2) +/- 8 KV direct discharge					
EMC Regulation	FCC, CE, BSMI, CCC					
<b>Accessory</b>						
	Charging & Communication cable / Charging & Communication Cradle / Pistol Grip / Four Slot Charging Base / Holster					

